

MODEL: R5K CANCEL STATION



R5KCANCEL



FEATURES

- One (1) Cancel button
- Flexible programming for call cancellation
- Continuous supervision of station
- Plug-in connector for easy service
- Optional antimicrobial Bio-seal to cover button and allow for easy disinfecting of the station

SPECIFICATIONS

Power Required: 8mA @ 15.5VDC

Weight: 1.92 oz (54 g)

Size: W: 3.2" (8.1 cm)

H: 4.25" (10.8 cm)

D: 0.6" (1.5 cm) in back box: 0.5" (1.3 cm) off-wall

Housing and Finish: Polycarbonate ABS, UL 94-5VA; light grey faceplate

Backbox Requirement: 1-gang, Non-gangable [W: 2.25" (5.7 cm) H: 4" (10.2 cm) D: 3.5" (8.9 cm)]

Certification: Designed for compliance to ANSI/UL 1069, IEC 60950-1, CE, RoHS / WEEE Compliant. Assembled in a U.S. FDA Registered facility.

Controls: One (1) push button for call cancellation.

Terminations: Plug-on connector

DESCRIPTION

The Responder® 5000 Cancel Station provides a single cancel button typically used for room-wide call cancellation. This station is normally located in a resident room near the door for easy call cancellation upon entry into the room.

The Cancel Station is connected to its associated corridor light and is continually supervised for station presence. Through programming, a "Trouble" message can annunciate at the associated console(s) when the station is removed from the system.



Rauland
A Division of AMETEK, Inc.
www.Rauland.com

Toll Free +1 800 752 7725
From Outside the U.S. +1 847 590 7100

*Architect and Engineer (A&E) Specifications available online at customerconnection.rauland.com
Specifications subject to change without notice.*